

Version : 07/2024

**produktbeskrivelse**

		Herringbone	XL	XXL long
V-fuge	-	4	2	2
eik overflatens tykkelse (+0/-0,1)	mm	0,6		
garanti, hjemlig miljø	-	20 years		
Klassifisering	ISO 10874	23 (stor hjemlig slitasje) 33 (stor offentlig slitasje)		
total tykkelse	mm	9,5	10	10
total vekt	kg / m <sup>2</sup>	8,5	8,5	8,5
dimensjon	mm	84 x 504	185 x 1190	210 x 2200
per pakke	m <sup>2</sup> / packs	20 planker (6.22 kg, 0.846 m <sup>2</sup> )	10 planker (18.7 kg, 2.20 m <sup>2</sup> )	6 planker (23.7 kg, 2.77 m <sup>2</sup> )
per pall	-	48 pakker	40 pakker	40 pakker
palldimensjon	hxlxl / mm	732 x 1200x 815	950 x 960 x 1200	750 x 960 x 2250

**testresultat**

fukttinnhold	-	7 - 10%		
låsesystem	-	OmniLoc	BestLoc X-Treme	
overflatebehandling	-	Ultimtec høytytelseslakk		
slitestyrke	XP B 53-669	+ 15 000 Tour (TT CS10)		
glansgrad	Gloss 60	5+/-2 (mat)		
kompatibel med gulvvarme	-	kompatibel med elektriske og vannbårne systemer		
termisk motstand	m <sup>2</sup> .K/W	0,055	0,052	
brannklassifisering	EN 13 501-1 (chêne)	Cfl-s1		
CE merking	EN 14342	CE		
Formaldehyd emisjon	EN 717-1	E1		
VOC emisjon	ISO 16 000-9	M1 / A	M1 / A+	
miljøprogram	Sertifisering	PEFC/07-31-229	PEFC/10-31-1047	





Version : 07/2024



**parqwood xl & xxl long**



**parqwood herringbone**

**strong wood floors.**